

LIFELIKE MOVIES AND MUSIC AWAITS YOU

Light, yet with extreme rigidity, our new Kevlar® woofer* cones' skin delivers clear and natural low distortion mid-range sound even during high volume play. Meanwhile AR's silk dome tweeters utilize titanium-fiber thread to help produce outstanding highs with precise imaging. Not your typical "in-wall" speakers.




Each Invizibo models' custom AR crossover ensures high-fidelity, high-output and low-distortion merge as one. Along with our high-tech cones, AR's typically oversized woofer "motors" combine both power-handling and efficiency needed for today's multichannel systems.




NOT JUST "EASY" INSTALLATION ... THE EASIEST

Nothing wimpy in these speakers. AR's robust injection-molded mounting lock system kills vibration and allows quick, trouble-free installation in standard walls.




| DESIGN | 1000 - K3 | 1000 - K5 |
|-------------------------------|--|--|
| DRIVE UNIT | Two-way enclosure | Two-way enclosure |
| FREQUENCY RESPONSE ± 3 DB | 2 x 13 mm Mylar tweeter, 1 x 6.5 in. paper cone mid/woofer | 4 x 13 mm Mylar tweeter, 1 x 6.5 in. paper cone mid/woofer |
| SENSITIVITY | 100Hz-35kHz | 100Hz-35kHz |
| NOMINAL IMPEDANCE | 92dB | 91dB |
| RECOMMENDED AMPLIFIER POWER | 4 Ω | 4 Ω |
| POWER HANDLING (CONTINUOUS) | 80W | 80W |
| DIMENSIONS (H X D X W) | 110W | 120W |
| FINISH | 334x 109 x 334 mm | 483 x 109x 317mm |
| NET WEIGHT | Satin black | Satin black |
| | 5.6 kg | 6.8 kg |




| DESIGN | 1000 - K7 |
|-------------------------------|---|
| DRIVE UNIT | Two-way enclosure |
| FREQUENCY RESPONSE ± 3 DB | 4 x 13mm Mylar tweeter, 1 x 6.5 in. paper cone mid/woofer |
| SENSITIVITY | 100Hz-35kHz |
| NOMINAL IMPEDANCE | 91dB |
| RECOMMENDED AMPLIFIER POWER | 4 Ω |
| MAXIMUM INPUT POWER | 80W |
| DIMENSIONS (H X D X W) | 120W |
| FINISH | 284 x 92 x 343 mm |
| NET WEIGHT | Satin black |
| | 4 kg |


| |
|-------------------------------|
| DESIGN |
| DRIVE UNIT |
| FREQUENCY RESPONSE \pm 3 DB |
| SENSITIVITY |
| NOMINAL IMPEDANCE |
| RECOMMENDED AMPLIFIER POWER |
| POWER HANDLING (CONTINUOUS) |
| DIMENSIONS (H X D X W) |
| FINISH |
| NET WEIGHT |




| |
|--|
| 2000-S2 |
| Two-way sealed enclosure |
| 2 x 30 mm textile dome tweeter 1 x 6.5 in. mid/woofer |
| 70Hz-22kHz |
| 90dB |
| 4 Ω |
| 100W |
| 180W |
| 310 x 98 x 508 mm |
| Satin black |
| 8.1 kg |



| |
|--|
| 2000-S3 |
| Two-way sealed enclosure |
| 4 x 30 mm textile dome tweeter 1 x 6.5 in. mid/woofer |
| 70Hz-22kHz |
| 90dB |
| 4 Ω |
| 100W |
| 180W |
| 310 x 98 x 508 mm |
| Satin black |
| 8.4 kg |



| |
|--|
| 2000-S4 |
| Two-way sealed enclosure |
| 4 x 30 mm textile dome tweeter 2 x 6.5 in. mid/woofer |
| 70Hz-25kHz |
| 89dB |
| 4 Ω |
| 150W |
| 250W |
| 410 x 98 x 508 mm |
| Satin black |
| 10.5 kg |



| |
|--|
| 2000-S6 |
| Two-way sealed enclosure |
| 8 x 30 mm textile dome tweeter 2 x 6.5 in. mid/woofer |
| 70Hz-25kHz |
| 89dB |
| 4 Ω |
| 150W |
| 250W |
| 410 x 98 x 508 mm |
| Satin black |
| 11 kg |

| |
|-------------------------------|
| DESIGN |
| DRIVE UNIT |
| FREQUENCY RESPONSE \pm 3 DB |
| SENSITIVITY |
| NOMINAL IMPEDANCE |
| RECOMMENDED AMPLIFIER POWER |
| POWER HANDLING (CONTINUOUS) |
| DIMENSIONS (H X D X W) |
| FINISH |
| NET WEIGHT |

AR

HIGH FIDELITY AUDIO

2017-2018



1000

1000-K3

1000-K5

1000-K7



INVIZIBO CUSTOM INSTALLATION SERIES



MODEL IR52
2-WAY DESIGN Carbon fiber cone woofer /silk and aluminum dome tweeter
TWEETER 1 x 25 mm
MIDRANGE / WOOFER 2 x 5.25" woofer
SENSITIVITY 90dB
MAXIMUM POWER 110W
IMPEDANCE 8Ω
RECOMMENDED AMPLIFIER POWER 80 W
FREQUENCY RESPONSE ± 3DB 55Hz-20kHz
SPECIAL APPLICATION Adjustable frame
DIMENSIONS (L x W x D) 381 x 275 x 155 mm
MOUNTING DIMENSIONS (L x W x D) 351 x 245 x 148 mm
NET WEIGHT 2.9 kg



MODEL IR63M
3-WAY DESIGN Kevlar cone woofer/Kevlar midrange /silk dome tweeter
TWEETER 1 x 25 mm
MIDRANGE/WOOFER 1 x 4"midrange 1 x 8" woofer
SENSITIVITY 92dB
MAXIMUM POWER 200W
IMPEDANCE 8Ω
RECOMMENDED AMPLIFIER POWER 80W
FREQUENCY RESPONSE ± 3DB 50Hz-25kHz
SPECIAL APPLICATION High frequency controller 0/-3/-6dB
DIMENSIONS (L x W x D) 357 x 255 x 104 mm
MOUNTING DIMENSIONS (L x W x D) 324 x 222 x 91 mm
NET WEIGHT 3.5 kg



MODEL IR63
3-WAY DESIGN Kevlar cone woofer / paper cone midrange / silk dome tweeter
TWEETER 1 x 25 mm
MIDRANGE / WOOFER 1 x 5.25"midrange 1 x 6.5" woofer
SENSITIVITY 91dB
MAXIMUM POWER 120W
IMPEDANCE 6Ω
RECOMMENDED AMPLIFIER POWER 90W
FREQUENCY RESPONSE ± 3DB 50Hz-20kHz
SPECIAL APPLICATION High frequency controller 0/-3/-6dB
DIMENSIONS (L x W x D) 360 x 210 x 93 mm
MOUNTING DIMENSIONS (L x W x D) 330 x 180 x 85 mm
NET WEIGHT 3.4 kg



MODEL IC62
2-WAY DESIGN Kevlar cone/silk dome tweeter
TWEETER 1 x 25 mm
MIDRANGE/WOOFER 1 x 6.5" woofer
SENSITIVITY 89dB
MAXIMUM POWER 100W
IMPEDANCE 8 Ω
RECOMMENDED AMPLIFIER POWER 80W
FREQUENCY RESPONSE ± 3DB 100Hz-20kHz
SPECIAL APPLICATION Tweeter direction adjustable/
High frequency controller 0/-3/-6dB/
Adjustable frame
DIMENSIONS (Ø x D) 244 x 138 mm
MOUNTING DIMENSIONS (Ø x D) 220mm x 118 mm
NET WEIGHT 1.6kg



MODEL IC82
2-WAY DESIGN Kevlar cone/silk dome tweeter
TWEETER 1 x 25 mm
MIDRANGE/WOOFER 1 x 8"woofer
SENSITIVITY 92dB
MAXIMUM POWER 160W
IMPEDANCE 8Ω
RECOMMENDED AMPLIFIER POWER 80W
FREQUENCY RESPONSE ± 3DB 100Hz-20kHz
SPECIAL APPLICATION Tweeter direction adjustable/
High frequency controller 0/-3/-6dB/
Adjustable frame
DIMENSIONS (Ø x D) 289 x 160 mm
MOUNTING DIMENSIONS (Ø x D) 265 x 143 mm
NET WEIGHT 2.8kg



MODEL
SATELLITE BOX UNIT
SENSITIVITY
MAXIMUM POWER
IMPEDANCE
RECOMMENDED AMPLIFIER POWER
FREQUENCY RESPONSE \pm 3DB
SPECIAL APPLICATION
DIMENSIONS (L x W x D)
NET WEIGHT

IS30
1x3.5" Full frequency
92dB
100W
4 Ω
50W
160Hz-20kHz
Adjustable wall bracket
117x111x101 mm
0.7kg



MODEL
SUBWOOFER
CABINET DESIGN
FREQUENCY RESPONSE \pm 3DB
AMPLIFIER POWER - RMS
AMPLIFIER POWER - DYNAMIC
CROSSOVER ADJUSTMENT
PHASE ADJUSTMENT
AUTO ON/OFF
CONNECTION
DIMENSIONS (H x W x D)
NET WEIGHT

RX-2010
10 in. air-dried paper cone
Front firing rear ported
28Hz-240Hz
200W
450W
40Hz-200Hz
0-180°
Yes
Speaker level inputs, Line inputs
309 x 296 x 330 mm
9.28kg



INVIZIBO

CUSTOM INSTALLATION SERIES

AR
Acoustic
Research®





RX

RX-2010 RX-2012 RX-2512



X

X3-10 X3-12 X5-12 X10-12



IS 5.1 HOME THEATER AUDIO BOX WITH 10" ACTIVE SUBWOOFER

**BUILD YOUR
HOME THEATER
WITH AR**



RADICALLY SMALL, RADICAL SOUND.

Both innovative and tried-and-true AR technology abounds in the petite Invizibo 5.1 audio system. Joining an advanced 3.5" full-range driver featuring a delicately balanced wool felt cone, is an overbuilt motor powered by a beefy 60mm-diameter magnet.

We think AR's subtle contemporary design is rather more stylish than your standard micro-speaker too. The curvaceous, AR air-suspension enclosures, are fist-sized wonders delivering what customers and audio critics all demand – balance, power and accuracy.

FLEXIBLY SMALL, FOR DISCREET PLACEMENT AND OPTIMAL SOUND

Whether they're beside your TV, discreetly tucked into a corner, the discreet IS30 speakers' low-profile style easily integrates into your home's décor both visually and acoustically. AR's stoutly built mounting brackets thoughtfully allow a virtual 360° swivel, for simple optimal acoustically correct placement anywhere in the room.



**360° angle
adjustable**

SEAMLESSLY INTEGRATED DEEP BASS

The RX-2010 sub is designed around an impressive long-throw 10" woofer, and paired with a gutsy, nicely featured 200 Watt digital amplifier. Tuned to deliver precise, dynamic in-room response to 28Hz or lower, it's anything but a "standard" subwoofer. This is bass you feel as much as hear.

That incredible depth makes integration with the IS30 speakers critical in the upper ranges naturally. So unsurprisingly our engineers ensured the high bass response of the RX subwoofer family yields a naturally seamless AR soundstage.



2000

2000-S2 2000-S3 2000-S4 2000-S6

AR
*Acoustic
Research*

