



High-end floor-standing loudspeakers with full-range driver and high level of efficiency

- The latest development standards and technology ensure a state of the art configuration for this classic construction
- Can be combined optimally with transistor and tube amplifiers from 5 watts per channel
- Attractive flat-design enclosure, floating appearance through all-metal design foot construction

HECO

### Direkt EINKLANG



Solidly built, multiple strutted MDF flat enclosure with attractive



Double bass-reflex design with bi-directional airflow-optimized rounded downfire tubes for maximum bass performance



Specially designed tweeter cone with newly developed NAWI shape and inverted dust cap ensures a fine and precise reproduction of the treble range



High-quality all-metal connector terminal with stable, goldplated high-end screw terminals











### **HIGHLIGHTS**

High-end floor-standing loudspeakers with full-range driver and high level of efficiency

- Exclusive one-way system with an excellent level of efficiency and superior spatiality
- The latest development standards and technology ensure a state of the art configuration for this classic construction
- Can be combined optimally with transistor and tube amplifiers from 5 watts per channel
- Attractive flat-design enclosure, floating appearance through all-metal design foot construction

### Drivers

- Extremely lightweight HECO kraft paper cone
- Specially designed tweeter cone with newly developed NAWI shape and inverted dust cap, manufactured from a single piece of material consisting of a particularly rigid and lightweight paper mixture. This ensures a fine and precise reproduction of the treble range
- Powerful dual-ferrite drive system and highly resilient, weight-optimized 25 mm CCAW voice coil
- Extremely low-loss, lightweight rubber surround
- Sturdy die-cast aluminum basket with narrow aerodynamic struts and numerous air vents
- A Kapton voice coil mount eliminates eddy current and ensures a highly defined sound patter
- Impedance compensation to minimize distortions in the mid-range and treble frequency
- Magnet system linearized with the high-tech Klippel<sup>®</sup> measuring system for ideal symmetry and minimal distortions



### Cabinet

- Stylish semi-matt lacquer finish with contrasting double stripes on the front
- Solidly built, multiple strutted MDF flat enclosure with attractive curves
- Specially designed all-metal foot construction for an absolutely stable base
- Floor-protecting rubber feet and all-metal spikes included
- Double bass-reflex design with bi-directional airflowoptimized rounded downfire tubes for maximum bass performance

### Crossover

- Accurate frequency response correction with high-quality tight-tolerance components
- Linearized impedance curve with very little fluctuation for optimum behavior on tube and transistor amplifiers from 5 watts per channel
- High-quality all-metal connector terminal with stable, gold-plated high-end screw terminals



Principle
Equipment
Power Handling (RMS/Max)
Impedance
Frequency Response
Recommended Amplifier Output
Sensitivity
Cabinet surface
Dimensions (WxHxD)

Weight

Black & Black White & Silver 1-way bass reflex 8" fullrange driver 120/180 W 4 - 8  $\Omega$  32 - 19 200 Hz 5 - 180 W 94 dB Black & Black, White & Silver Cabinet 382 x 842 x 196 (224 incl. Terminal) mm Incl. metal spikes 382 x 931 x 385 mm 19.0 kg

Art. No. 135 0720 EAN: 40 29678 50720 4 Art. No. 135 0722 EAN: 40 29678 50722 8

