

MAC XTREME 2000

PACKAGE



MAC XTREME 2000

PACKAGE



MAC XTREME 2000

Highlights

Mac Xtreme Sub 110R

Enclosure

- Bass reflex subwoofer
- Air-flow optimized bass-reflex port
- Nickel-plated screw terminal
- Anti-skid carpet

Woofer

- 10" high power driver with ventilated pole core and 2" voice coil
- Low-resonance steel basket with additional voice coil ventilation
- PP design dustcap
- Multi-layer, coated paper cone

Mac Xtreme Amp 2000

- 2 ohm stable
- Variable low pass 50 – 250 Hz (12 dB per octave)
- Variable high pass 50 – 250 Hz (12 dB per octave)
- Switchable bass boost 6/12 dB at 45 Hz
- High level inputs
- Low level RCA outputs
- MONO / STEREO switch
- Bridge/tri-mode capability
- Protection circuit that safeguards against short circuits, DC-offset and overheating
- Green operation and red protection indication LED



PACKAGE

MAC XTREME 2000

MAC XTREME SUB 110R

Principle / DIN-Ø	Bass reflex subwoofer with 10" driver
Power Handling RMS/max.	250 /800 W
Impedance	4 Ω
Frequency Response	26 – 500 Hz
Sound Pressure Level	89 dB
Driver Material	Multi-layer coated paper cone
Dimensions (WxLxD)	370 x 300 x 230/280 mm
Weight	8 kg

MAC XTREME AMP 2000

Max. power output (sine burst 2:8, 1 kHz) into 4 ohms , 14.4V	2x 180 /1x 500 W
RMS power output (DIN 45 324) into 4 ohms, 14.4V	2x 60 /1x 160 W
Max. power output (sine burst 2:8, 1 kHz) into 2 ohms, 14.4 V	2x 250 W
RMS power output (DIN 45 324) into 2 ohms, 14.4V	2x 80 W
Frequency response	5 Hz – 50 kHz (-3 dB)
THD	< 0,05 % (1 kHz)
Signal-to-noise ratio (A-weighted)	> 100 dB
Input sensitivity	0.4 – 4 V
Input impedance	20 kOhms
Power supply	12 V negative ground
Dimensions (WxLxD)	219 x 59 x 226 mm
Weight	1,75 kg

PACKAGE