











Designation	Art. No.	Unit	Colour
Phono PreAmn Pro	6060	1 Pc	metallic brown

Phono PreAmp Pro

Low-distortion phono amplifier for record players with MM or MC pickup

The Phono PreAmp Pro from Oehlbach integrates your record player with an MM or MC cartridge into existing high-quality hi-fi components without a dedicated phono input. The low-noise preamp is fitted with gold-plated contacts to guarantee a stable and reliable connection between the phono device and the hi-fi system. Equipped with an external power supply, the Phono PreAmp Pro weights just 100 g and easily fits into any hi-fi rack thanks to its compact design. The individual components are connected via analogue stereo RCA connectors.

Available from february

Features

- √ 24- carat gold-plated contacts
- ✓ For moving-magnet pick-up
- ✓ For moving-coil pick-up
- ✓ Power supply via external power supply unit

Technical Data

 $\begin{array}{lll} \textbf{Operating current} & < 100 \text{ mA} \\ \textbf{Output voltage} & (\text{MM}) \ / \ (\text{MC}) \ 600 \ \text{mV} \\ \textbf{Input sensitivity} & (\text{MM}) \ 5\text{mV} \ / \ (\text{MC}) \ 0.5\text{mV} \\ \end{array}$

Weight 0,1 kg

 $\begin{array}{ll} \textbf{Balance des canaux} & (\text{MM}) < 0.5 \text{ dB} / (\text{MC}) < 0.5 \text{ dB} \\ \textbf{Channel Separation} & > 70 \text{ dB (MM)}, > 60 \text{ dB (MC)} \\ \end{array}$

Voltage supply 18V/DC, 150 mA

Distortion (MM) < 0.1 % / (MC) < 0.1 %

 $\begin{tabular}{lll} Permissible relative humidity: & 5% to 90% \\ Temperature range: & -15°C to +50°C \\ Signal-to-noise ratio & >72 dB (MM); >60 dB (MC) \\ Input impedance & (MM) 50 0hms (MC) 100 0hms \\ \end{tabular}$



