Monitor Active 2000



POWERED BLUETOOTH® STEREO LOUDSPEAKER SET WITH PHONO INPUT

Monitor Active 2000





POWERED BLUETOOTH® STEREO LOUDSPEAKER SET WITH PHONO INPUT

- Numerous connection options for flexible and versatile use for smartphone via Bluetooth®, record player, TV, etc.
- High-quality phono preamplifier for direct connection of a record player with MM magnet system
- Integrated high-performance amplifier module, no additional amplifier is required
- Powerful class D amplifier module with 2 x 35 watts RMS power
- Bluetooth® input (version 4.1) for high-quality music from mobile devices

Monitor Active 2000





ALL INCLUSIVE LOUDSPEAKER SYSTEM

An active speaker system can be used in many different ways, whether it's as a fully-fledged shelf speaker for hi-fi setups or as a monitor speaker for the desk. Such a system should also be flexible when it comes to inputs - and that's exactly what the Monitor Active 2000 is.

COMPACT AND POWERFUL

Active speakers are not only a universal problem solver, but they are also a technical stroke of genius. Music can be played from almost any source without additional electronic equipment, which reduces tedious cabling requirements and simplifies operation.

PERFECTLY COORDINATED PERFORMANCE

A 25 mm tweeter dome and a 125 mm bassmidrange driver are combined in each speaker. The complete package consisting of electronics and speaker technology produces an impressive sound and it eclipses many other systems in terms of flexibility.

Monitor Active 2000

POWERED BLUETOOTH® STEREO LOUDSPEAKER SET WITH PHONO INPUT

DRIVERS

- 25 mm fmax tweeter with soundguide for optimised dispersion properties and powerful ferrite drive for excellent dynamics
- FE-Dynamics bass-midrange driver with low partial oscillation, coated paper cone and distortion optimized magnet system

CABINET

- Very solid low-resonance construction made of E1 MDF panels
- Elegant design with high-quality black wood decor
- Detachable front cover with acoustic cloth
- Airflex port with rounded reflex opening for reducing wind noises
- Resonance-damping rubber feet

AMPLIFIER & CONNECTIONS

- Bluetooth[®] input (version 4.1)
- Analogue stereo input (Cinch R/L) with switchable phono preamplifier for direct connection of a record player with magnet system (MM)
- Additional 3.5 mm analogue stereo input for connecting portable audio devices
- Optical digital input for direct connection of digital audio devices (e. g. TV)
- Sampling rates of all digital inputs up to 24Bit/192kHz
- LED status indicator at the speaker front
- Control for volume and input selection at the rear panel of the right loudspeaker
- Complete control is ensured via the supplied remote control (incl. battery)
- Low standby power consumption (<0.5 watts) with auto standby function

CROSSOVER

- Amplitude- and phase-optimised crossover with high-quality components
- High-quality terminal with solid gold-plated and capsulated screw connectors





Monitor Active 2000

MONITOR ACTIVE 2000 2-way bass reflex, active

DRIVERS 1 x 5" woofer- midrange, 1 x 1" dome-tweeter

POWER HANDLING (RMS/MAX) Active

POWER OUTPUT (RMS/MAX) 2 x 35 / 2 x 70 watts

IMPEDANCE Active

FREQUENCY RESPONSE 38 – 40.000 Hz

CROSSOVER FREQUENCY 3.500 Hz

MAINS VOLTAGE 100 - 240 V

OPERATING FREQUENCY 2402 – 2480 MHz

MAXIMUM EMITTED POWER (EN 62479) 2.97 dBm

CABINET SURFACE Front: Black satin Cabinet: Black decor

DIMENSIONS (WxHxD) 175 x 290 x 205 mm

WEIGHT Active speaker: 4.4 kg Passive speaker: 3.8 kg

ART.NO. /EAN Black: 172 700 / 40 18843 72700 4

